

SERIES

R3

BORE SIZE

H - 4" P - 10"
K - 5" R - 12"
L - 6" S - 14"
M - 7" T - 16"
N - 8"

ROD DIAMETER

J - 2" R - 5"
K - 2 1/2" S - 5 1/2"
L - 3" W - 7"
M - 3 1/2" X - 8"
N - 4" V - 9"
P - 4 1/2" Y - 10"

ROD THREAD STYLE

N2 - Intermediate Male
M2 - Intermediate Male Metric*

*Contact Cowan for size

CUSHIONS

5C - Adjustable both ends
6C - Adjustable head end
7C - Adjustable cap end
8 - None

CUSHIONS POS

Omit if non Cushion
CXX

XX denotes position
ex: 23 = Pos 2 head
Pos 3 Cap

DOUBLE ROD DIA

Omit if not required
DJ2 - 2" DR2 - 5"
DK2 - 2 1/2" DS2 - 5 1/2"
DL2 - 3" DW2 - 7"
DM2 - 3 1/2" DX2 - 8"
DN2 - 4" DV2 - 9"
DP2 - 4 1/2" DY2 - 10"

2nd ROD THREAD STYLE

RN2 - 2nd Rod: Intermediate Male
RM2 - 2nd Rod: Intermediate Male Metric*

*Contact Cowan for size

PORTS

GXX - SAE Code 62 flange
FXX - SAE Code 61 flange
SXX - SAE
NXX - NPT
BXX - BSPP
MXX - ISO

XX denotes position
ex: 12 = Pos 1 head,
Pos 2 Cap

SEALS

N - Standard Seals
F - High Temp
L - Low Temp
E - EPDM

MOUNTINGS

PR1 Cap Fixed Clevis (with Clevis pin)
PR3 Male Clevis (with pivot pin)
SR2 Side lugs
TR1 Head Trunnion
TR2 Cap Trunnion
TR4 Intermediate Trunnion
SRB Spherical Bearing
X0 No mount

OPTIONS

Please consult the factory for additional option codes

EXAMPLE

