

SERIES	BORE SIZE		ROD DIAMETER		ROD THREAD STYLE	CUSHIONS	CUSHIONS POS
R5	H - 4"	P - 10"	J - 2"	R - 5"	N2 - Intermediate Male	5C - Adjustable both ends	Omit if non Cushion
	K - 5"	R - 12"	K - 2 1/2"	S - 5 1/2"	M2 - Intermediate Male Metric*	6C - Adjustable head end	CXX
	L - 6"	S - 14"	L - 3"	W - 7"		7C - Adjustable cap end	
	M - 7"	T - 16"	M - 3 1/2"	X - 8"	*Contact Cowan for size	8 - None	XX denotes position
	N - 8"		N - 4"	V - 9"			ex: 23 = Pos 2 head
			P - 4 1/2"	Y - 10"			Pos 3 Cap

DOUBLE ROD DIA	2ND ROD THREAD STYLE	PORTS	SEALS	MOUNTINGS
Omit if not required	RN2 - 2nd Rod: Intermediate Male	GXX - SAE Code 62 flange	N - Standard Seals	PR1 Cap Fixed Clevis (with Clevis pin)
DJ2 - 2" DR2 - 5"	RM2 - 2nd Rod: Intermediate Male Metric*	FXX - SAE Code 61 flange	F - High Temp	PR3 Male Clevis (with pivot pin)
DK2 - 2 1/2" DS2 - 5 1/2"		SXX - SAE	L - Low Temp	SR2 Side lugs
DL2 - 3" DW2 - 7"		NXX - NPT	E - EPDM	TR1 Head Trunnion
DM2 - 3 1/2" DX2 - 8"		BXX - BSPP		TR2 Cap Trunnion
DN2 - 4" DV2 - 9"	*Contact Cowan for size	MXX - ISO		TR4 Intermediate Trunnion
DP2 - 4 1/2" DY2 - 10"				SRB Spherical Bearing
				X0 No mount

OPTIONS

Please consult the factory for additional option codes

XX denotes position
ex: 12 = Pos 1 head,
Pos 2 Cap

EXAMPLE

